



# PRODUCT DATA SHEET

Protective treatment - Pore filler

## Wetrok Porosol

The pore filler for long-lasting protective treatments





# Wetrok Porosol



**pH value (Concentrate):** 7.8–8.8

**Important ingredients:**

Polymers, Waxes, Solvents, Surfactants, Preservatives

**Recommended dosage:**



**Pore filling**

Undiluted

**METHODS  
finder**



**APPLICATION**

- The pore filler for durable, long-lasting protective treatments
- For treating all porous surfaces (natural and artificial stone, asphalt, hard concrete, coarse ceramic, xyloolith, linoleum, etc.)

**PROPERTIES**

- Closes the pores of floor coverings
- Improves cleanability
- Water vapour diffusion guaranteed
- Semi-permanent (difficult to remove)
- Wet effect (colour deepens)

**GOOD TO KNOW**

- Reduces drying times on treated floors, as well as consumption of coating materials on older linoleum floors
- Consumption: 25 - 50 g/m<sup>2</sup>

**PLEASE NOTE**

- Shake well before use
- Not suitable for water and damp-sensitive floor coverings (e.g. anhydrite), for outdoor areas and wet zones
- Apply at a temperature of 15-25°C and 30-70% relative humidity
- Before each use, make sure that the floor covering is pH-neutral

**RECOMMENDED APPLICATION METHOD**

**Filling pores (protective treatment)**

The floor covering must be free of all previous coatings, absorbent/porous and completely dry (<3% residual moisture, CM method). Dry vacuum/mop the floor covering to collect dust. Use the application tool to apply a thin coating of the pore filler on the entire surface. The product must soak in. Wipe off excess product. Drying time: at least 2 h. Important: Check the pore sealing effect using a water test. Use a suitable coating agent to treat the floor coverings.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use. Protect against frost.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.