



# PRODUCT DATA SHEET

Floor cleaning - Industrial and deep cleaners

## Wetrok Antiwax forte

The gentle high-performance industrial cleaner from the Antiwax family - combining a strong performance with increased work safety and greater environmental compatibility





# Wetrok Antiwax forte



**pH value (Concentrate):** 8–9

**Important ingredients:**

Surfactants, Solvents, Soap, Fragrances

**Recommended dosage:**



**Maintenance cleaning**

0.05 –0.1 l/10 l



**Intermediate cleaning**

0.1–0.2 l/10 l



**Deep cleaning**

3–5 l/10 l

**Wax removal**

1 l–3 l/10 l

**METHODS  
finder**



**APPLICATION**

- High-performance deep and industrial cleaner
- For the removal of oil, grease and general industrial soiling
- For cleaning washable and solvent-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, etc.)
- Also suitable for cleaning non-sealed wood floors
- Can also be used for removal of polymer and wax coatings

**PROPERTIES**

- Low lather
- Slightly alkaline
- Scented
- Contains solvents

**GOOD TO KNOW**

- The right choice where a wide range of difficult cleaning jobs must be performed with an increased level of work safety and in a more environment-friendly manner.

**PLEASE NOTE**

- Not suitable for maintenance cleaning of self-shine floor coverings
- Use a maximum concentration of 5% on varnished surfaces or elastomers (synthetic or natural rubber)

**RECOMMENDED APPLICATION METHOD**

**Basic cleaning**

**Scrub drying in a single work step**

**Wet mopping, two-step process**

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.