



# PRODUCT DATA SHEET

Floor cleaning - Maintenance cleaners

## Wetrok Reshine

Very powerful and versatile maintenance cleaner certified according to DIN 18032 - strong, quick wetting for streak-free results, protects the floor's shine





# Wetrok Reshine





**pH value (Concentrate):** 9–10


**Important ingredients:**

Surfactants, Soap, Solvents, Chelating agents, Fragrances, Preservatives

**Recommended dosage:**

 **Maintenance cleaning**  
0.1–0.2 l/10 l

 **Intermediate cleaning**  
0.2–0.5 l/10 l

 **Removal of adhesive agents**  
1.0 l/ 10 l

METHODS  
finder



**APPLICATION**

- For maintenance cleaning of washable and alkali-resistant surfaces and floor coverings (PVC, natural and artificial stone, clinker, asphalt, linoleum, natural rubber, etc.)
- Very high-performance, versatile maintenance cleaner

**PROPERTIES**

- Low lather
- Slightly alkaline
- Lightly scented
- Protects the floor's shine
- Conforms to DIN 18032

**GOOD TO KNOW**

- Reduces microcracks and ensures a uniform appearance
- When removing adhesive (handball resin) from sports floor coverings, first check the playing field markings for chemical compatibility, allow the 10% Reshine solution to take effect for 15 minutes

**RECOMMENDED APPLICATION METHOD**

**Scrub drying in a single work step**

Pour the cleaning solution into the fresh water tank. Remove any loose dirt by means of dust-binding mopping/dry vacuuming. Scrub-dry the floor covering thoroughly with a scrubber-dryer and a suitable pad or brush.

**Wet mopping, single work step**

Remove any loose dirt (e.g. dust-binding mopping/dry vacuuming). Soak the mop with cleaning solution, wring it out well, or use a pre-wetted mop. Wet mop the floor covering.

**STORAGE**

Store in original container at 15 to 25°C and protected from sunlight. Keep container closed when not in use.

*Durability (unopened): 24 Month*

Wetrok AG shall have no liability whatsoever for damage caused by incorrect use. Observe special cleaning and care instructions from the floor covering manufacturer.